



RALLY 14 0260 N1401E

WARNING
PILOT WEATHER MUST BE ON WHEN OPERATING BELOW 40' IN
INSTRUMENT METEOROLOGICAL CONDITIONS

THIS AIRCRAFT HAS BEEN CHECKED BY THE INSTALLATION
FOR A VOR OPERATIONAL TEST AND FOUND TO BE OPERATING
AS A NORMAL. FOR UTILITY CATEGORY AIRCRAFT USE IN COMPLIANCE
WITH THE OPERATIONAL LIMITATIONS AS STATED IN THE FORM
OF PLACARD, WARNING, AND MANUALS.

FUEL QTY. FUEL QTY.

40GALS USABLE

AL. TEMP. PRESS. PSI.

AFF ATIS - 128.325 COS ATIS - 134.0
AFF GND - 134.325 COS APP - 120.0
AFF TUR - 127.55 FLY ATIS - 125.65
SKYTRAKR 127.55 FLY CTAF - 122.7
EAGLE - 127.000 FCS TWR - 125.0

AMPERES

HIGH VOLTAGE

CONTROL LOCK
REMOVE BEFORE
STARTING ENGINE

TAKEOFF

NOSE
UP

CARBURETOR ICE DETECTOR

skyhawk II