



RALLY 14 0260 N1401E

WARNING  
PISTON HEATER MUST BE ON WHEN OPERATING BELOW 40' IN  
INSTRUMENT METEOROLOGICAL CONDITIONS

THIS AIRCRAFT HAS BEEN EQUIPPED BY THE INSTALLATION  
SHOP & IS NOT TO BE OPERATED WITHOUT THE INSTALLATION  
SHOP'S APPROVAL. FOR OPERATIONAL INFORMATION, SEE THE  
OPERATING MANUAL. FOR OPERATIONAL INFORMATION, SEE THE  
OPERATING MANUAL. FOR OPERATIONAL INFORMATION, SEE THE  
OPERATING MANUAL.

FUEL QTY. 40GALS USABLE

60 80 100  
PRESS. PSI

AFF ATIS - 128.325 COS 8705 - 134.0  
AFF GND - 130.25 COS APP - 130.0  
AFF TRAF - 130.25 FLY ATIS - 130.005  
SKYHAWK 127.25 FLY CTAF - 132.7  
EAGLE - 127.05 FCS 7906 - 132.0

AMPERES

HIGH VOLTAGE

CONTROL LOCK  
REMOVE BEFORE  
STARTING ENGINE

TAKEOFF

BOOST

CARBURETOR ICE DETECTOR

skyhawk II